

TINGLEY

est. 1896

Badger Boots™ Steel Toe Knee Boot

Style Number - 87251

Compliance Standards: ASTM F2413 M/IC EH*
ASTM F3445 SR



Product Detail: Steel toe provides toe impact and compression protection,. Features a cushioned footbed to absorb impact shock and a steel shank for added arch support. Quality rubber, neoprene and airmesh construction is 100% waterproof and durable. Ultra comfortable, breathable upper with extra width in the calf for a relaxed fit. Slip resistant per ASTM F3445, the standard specification as of July 2021.

**Boot shall withstand 18,000 volts at 60 HZ for 1 minute with no current flow or leakage current in excess of 1.0 milliamperes under dry conditions tested as per lab conditions in Test Method F2412. Electrical Hazard soles and heels are intended to reduce the hazards due to accidental contact with live electrical circuits, electrically energized conductors, parts or apparatus. Electrical Hazard soles and heels are not intended for wear in those work environments where volatile chemicals or explosives may be present, where conductive Footwear is required. Warning: Electric Hazard features of the soles and heels will deteriorate in wet environments, and when worn with excessive wear on the soles and heels.*

Product Type: Knee Boot

Insole: Removable, cushioned insole helps wick moisture to keep feet warm and dry.

Sizes: US Men's 4 through 14

Outsole Tread Pattern: Self-cleaning cleated outsole provides traction on indoor and outdoor surfaces.

Color: Black Upper / Black Outsole

Appearance: Boots are clean and free from obvious defects, flash and contamination. The surfaces are visually consistent in texture and contrast with no evidence of foreign material or distortion. Molded products are fully formed, well defined and properly aligned, with level outsoles, smooth seams and neatly trimmed edges. Colors are consistent within and between lots.

Material: Hand-Plied Vulcanized Rubber overlaid on Neoprene

Closure Type: None

Labeling: Lot code, country of origin, and size are marked on the outsoles. Printed hangtag displays name, space for retail pricing, and product features and benefits. Boots are labeled to indicate compliance with ASTM F2413, F3445 and California Prop 65.

Packaging: Boots are pair packed into a labeled carton for individual pair handling or retailing. Packaged four (4) pairs per labeled, corrugated cardboard case.

Applications: Suited for various jobs within Construction, Municipalities, Public Works, Transportation, Utilities, Farm and Barn, Agriculture, and General Industry.

Chemical Resistance: Acids, alkalis, alcohols, and dilute solutions of most chemicals that are water-soluble.

Not recommended for constant contact with petroleum and oil-based products.

Country of Origin: China

Other: Testing and certification documents are available upon request from Tingley Rubber Corporation.

Dims & Weight by Size:	M4 W6	M5 W7	M6 W8	M7 W9	M8 W10	M9 W11	M10 W12	M11 W13
Height (in.)	14.5	14.5	14.5	14.5	15.2	15.2	15.2	15.2
Ball Width (in.)	4.0	4.1	4.2	4.3	4.3	4.5	4.7	4.7
Heel-to-Toe (in.)	10.6	10.8	11.1	11.3	11.7	12.1	12.2	12.7
Topline Circumference (in.)	13.4	13.8	14.2	14.6	15.0	15.4	15.8	16.1
Weight (lbs)	6.7	6.8	6.9	7.0	7.1	7.2	7.3	7.4

Dims & Weight by Size:	12	13	14
Height (in.)	15.2	15.2	15.2
Ball Width (in.)	4.8	4.9	5.0
Heel-to-Toe (in.)	13.0	13.4	13.8
Topline Circumference (in.)	16.5	16.9	17.3
Weight (lbs)	7.5	7.6	7.7

Case Pack: 4 pairs

Package Dimensions:

	Inner Carton (L x W x H)	Case Carton (L x W x H)
Sizes 4 to 7	19 x 13 x 5 in	20 x 13 x 20 in
Sizes 8 to 11	20 x 14 x 5 in	21 x 15 x 21 in
Sizes 12 to 14	20 x 15 x 5 in	22 x 16 x 21 in