

EP08 - Corded PU Foam Ear Plug

Collection: Ear Plugs
Range: Hearing Protection
Materials: PU Foam, PVC
Inner Pack: 200
Outer Carton: 10

Product information

Disposable ear plugs made from soft PU foamCorded for safe keepingEach pair inside individual hygienic polybagExcellent attenuation rate

Hearing Protection

Hearing problems occur when you are exposed to hazardous working conditions without wearing the correct protective equipment.

Standards

EN 352-2 (SNR 36dB)
ANSI S3.19 (32dB)



Features

- CE-CAT III
- Retail box which aids presentation for retail sales
- Individually packed for vending machines

Colors

	Range
Orange	-

PORTWEST[®]

PRODUCT SPECIFICATION & TECHNICAL DATA

EP08 - Corded PU Foam Ear Plug

Commodity Code: 6506101000

Test House

Michael & Associates, Inc. (Notified Body No.:)
2766 W. College Ave Suite 1
PA 16801, United States
Cert No: Q1441A

ALIENOR CERTIFICATION (Notified Body No.: 2754)
ZA du Sanital
86100 , France
Cert No: 2754/1246/159/06/18/0288

CARTON DIMENSIONS/WEIGHT

Item	Colour	Len	Wid	Hgt	Weight (Kg)	Cubic (m ³)	EAN13	DUN14
EP08ORR	Orange	65.0	35.0	33.0	0.7600	0.0751	5036108183852	15036108622419

PERFORMANCES - SOUND ATTENUATION - EN352-2:2002

EP02/EP08/EP30								
A	Frequency (Hz)	125	250	500	1000	2000	4000	8000
B	Means Attenuation (dB)	36.5	34.2	39.1	37.8	39.6	44.9	46.2
C	Standard Deviation (dB)	4.7	4.5	4.8	5.8	4.0	6.4	6.2
D	Assumed Protection (dB)	31.7	29.7	34.2	32.0	35.5	38.5	40.1
SNR = 36 dB H = 36 dB / M = 33 dB / L = 32 dB								

PERFORMANCES - SOUND ATTENUATION ANSI S.19-1974

Tested by Michael & Associates, Inc. – 400 Long Lane, PA Furnace, PA 16865, USA

EP02/EP08										
A	Frequency (Hz)	125	250	500	1000	2000	3150	4000	6300	8000
B	Means Attenuation (dB)	39.8	40.4	42.6	40.3	39.1	45.2	45.7	48.3	47.4
C	Standard Deviation (dB)	3.0	3.9	2.9	3.6	3.7	3.0	2.5	4.9	3.7
NRR (Noise Reduction Rating) = 32 dB										

EP08ORR