# **PORTWEST**

## **PRODUCT SPECIFICATION & TECHNICAL DATA**

### **PW40 - Classic Ear Protector**

**Collection:** Ear Muffs **Range:** Hearing Protection

Materials: ABS, Polycarbonate, PVC

Outer Carton: 60

### **Product information**

Classic design ear muffLight and robustIdeal for all day useExcellent attenuation rate

#### **Ear Muffs**

Portwest hearing protection range includes PPE with different level sound attenuation, to be adapted to various working environments giving the correct protection from dangerous noise, without isolating the workers. New models and colors for earmuffs allow a personalized choice. An updated range of earplugs complete our competitive and performing offer.

#### **Hearing Protection**

Hearing problems occur when you are exposed to hazardous working conditions without wearing the correct protective equipment.

#### **Standards**

AS/NZS 1270 (SLC(80) 28dB - Class 5) EN 352-1 (SNR 28dB) ANSI S3.19 (22dB)



#### **Features**

- CE-CAT III
- Lightweight and comfortable
- Adjustable length for a secure and comfortable fit
- Retail bag which aids presentation for retail sales
- 100% Metal free
- · Individually packed for vending machines

Colors								
	Range							
Red	-							
Yellow	-							

# **PORTWEST**

## **PRODUCT SPECIFICATION & TECHNICAL DATA**

PW40 - Classic Ear Protector Commodity Code: 6506101000

#### **Test House**

Michael & Associates, Inc. (Notified Body No.: ) 2766 W. College Ave Suite 1 PA 16801, United States

Cert No: Q3930A

BSI Group The Netherlands B.V. (Notified Body No.: 2797)

Say Building, John M. Keynesplein 9, 1066 EP

, Netherlands

Cert No: CE 698123 - I

#### CARTON DIMENSIONS/WEIGHT

Item	Colour	Len	Wid	Hgt	Weight (Kg)	Cubic (m³)	EAN13	DUN14
PW40RER	Red	62.0	44.0	51.0	0.1600	0.1391	5036108134656	15036108636201

## **PERFORMANCES - SOUND ATTENUATION - EN 352-1:2002**

P۱	N40/PS40	<b>SNR 27.6dB H:</b> 29.2 <b>M:</b> 25.4 <b>L:</b> 17.9								
Α	Frequency (Hz)	63	125	250	500	1000	2000	4000	8000	
В	Mean Attenuation (dB)	18.1	15.0	18.3	26.8	37.5	29.5	35.8	36.1	
C	Standard Deviation (dB)	4.1	2.7	3.3	2.0	4.1	2.9	3.3	5.8	
D	Assumed Protection (dB)	14.0	12.3	15.0	24.8	33.4	26.6	32.5	30.3	

PW40RER